

Frameless Construction Specifications

1 CABINET BOX CONSTRUCTION

3/4" thick double-sided TFL (thermofused laminate particleboard).
Front face is edgebanded with 1mm PVC matching door finishes. 8mm wood doweled construction with a 1/4" thick TFL back.

All Open Stained/Painted Cabinets use a 3/4" thick maple plywood box with a 1/4" back.

2 Shelves

3/4" thick double-sided TFL (thermofused laminate particleboard) with matching 1 mm PVC edgeband. All shelves are adjustable on 5 mm pins.

3 Door & Drawer Fronts

-Slab:

3/4" thick double-sided TFL (thermofused laminate particleboard) slab doors and drawer fronts with 1/8" reveals. Grain runs vertically on all doors and drawer fronts. Edgebanded on all sides.

-5 Piece Maple:

3/4" thick Cope and Stick doors and drawer fronts. Eased edges with 1/8" reveals.

Door Frame Size: 2-3/8"

Drawer Front Frame Size: 1-1/2" Top and Bottom

-MDF:

3/4" thick routed MDF doors and drawer fronts with 1/8" reveals.

Soft-closing, Concealed hinge, 105 degree, 4-way adjustable. No decorative hardware is supplied.

4 Toe kick

4" high x 3 1/2" recessed from front face of cabinet box.

5 Drawers

5/8" thick double-sided TFL (thermofused laminate particleboard) with 1 mm PVC edgeband.

Concealed undermount soft-closing slides with a load capacity of 100 lbs. Built-in drawer bumpers. 8mm wood doweled construction.

